

LED Linear T8: 2', 3' & 5' UL 1598C

Stock No.	Product Description
LED-6110-00-UL-2-NW-N	FL24-120/277-10-132-NW 2' 3000K
LED-6111-00-UL-2-CW-N	FL24-120/277-10-132-CW 2' 4000K
LED-6112-00-UL-2-DL-N	FL24-120/277-10-132-DL 2' 5700K
LED-6119-00-UL-3-NW-N	FL36-120/277-10-168-NW 3' 3000K
LED-6123-00-UL-3-CW-N	FL36-120/277-10-168-CW 3' 4000K
LED-6118-00-UL-3-DL-N	FL36-120/277-10-168-DL 3' 5700K
LED-6124-00-UL-5-NW-N	FL60-120/277-10-288-NW 5' 3000K
LED-6126-00-UL-5-CW-N	FL60-120/277-10-288-CW 5' 4000K
LED-6125-00-UL-5-DL-N	FL60-120/277-10-288-DL 5' 5700K

10.0w = 17W
LED 2' Fluorescent T8

12.7w = 25W
LED 3' Fluorescent T8

26.0w = 40W
LED 5' Fluorescent T8

Description:
T8 Linear LED, fully encapsulated, replaces 2', 3', or 5' T8/T10/T12 fluorescent lamps. Suitable for both open and fully enclosed fixtures. Now classified under UL1598C which enables fixture to retain UL listing after modification.

- Power consumption: 10W(2'), 12.7W(3'), 26W(5')
- 120° Beam angle
- 120-277VAC Non-Dimmable
- G13 Base
- Available in 3000K, 4000K or 5700K CCT
- >80 CRI
- 50,000 Rated L70 LED life
- Single end hot/neutral, non-shunted G13 only
- UL Classified (US & CA) 1598C
- 5 Year warranty

Applications:
The 2', 3', and 5' Linear LED lamp has been designed to retrofit existing fluorescent troffer thereby reducing maintenance and energy expenditures - and as an energy saving light source for new fixtures and installations.

- Office Lighting
- Low Bay Lighting
- Sign Lighting
- Hospitality lighting
- Residential lighting


Note: When retrofitting LED to fluorescent fixture, ballast must be by-passed when present. Eliminating the ballast saves additional costs related to maintenance, energy consumption and performance. Additionally, by-passing ballast will insure no RFI interference.

Packaging: 24/Master Ctn.
Unit: 23.8" x 1.3" x 1.3" 2 Foot
Master: 25.8" x 14" x 6.1"

Unit: 36.02" x 1.3" x 1.3" 3 Foot
Master: 38" x 14" x 6.1"

Unit: 59.6" x 1.3" x 1.3" 5 Foot
Master: 61.6" x 14" x 6.1"

Now
Classified
UL1598C



Technical Specifications			
Bulb Type	T8/T10/T12	Mounting	G13
Bulb Material	Aluminum/Plastic	Beam Angle	120°
Power Consumption	2' 10.0 watts 3' 12.7 watts 5' 26.0 watts	LEDs:	2' 132 LEDS 3' 168 LEDS 5' 288 LEDS
Lumens	2' 850-1000 LM 3' 1000-1270 LM 5' 1900-2200 LM	Dimmable	No
Efficacy	>98 Lumens / watt	Replaces	17-40w Fluorescent
Rated LED Life	50,000 Hrs.	CCT	3000K 4000K 5700K
Power Factor:	>90	CRI:	> 80
IR / UV	None	Mercury/Lead Content	None
Warranty	5 year Limited	Dimensions	1.17" X 2', 3', 5' nominal

Note: All specification information falls within a ± 2% range and is subject to change without notice.

NOTE: Light Efficient Design is providing this information to the general public. Please note that all products contained herein are trademarked, copyrighted, and/or have patents pending. Any use of these designs is strictly prohibited without prior written consent. Light Efficient Design protects its proprietary information vigorously in the courts of the United States of America.



106 S. Wynstone Park Drive • N. Barrington, IL 60010
(847) 380-3540 • FAX: (847) 380-3542
www.led-llc.com