

LED-8077 150W High Bay Luminaire

150w = 400W
LED **MH / HPS**

Stock No.

LED-8077-50K

LED-8077-40K-HV

Product Description

150W High Bay, 5000K CCT

150W High Bay, 4000K CCT (200-480V)

Description:

150W LED High Bay luminaire with mounting brackets and hardware designed for high Bay applications. Compare to 400w HID.

- 150W consumption
- **DCL approved**
Replaces HID 400W
- 90° Beam
- 120-277VAC or 200-480V
- Non-Dimmable
- Available in 5000 CCT (HV model 4000K)
- 73 CRI
- 50,000 hr. rated L70 LED life
- Paint-free anodized finish
- IP65 Rated
- Operating temp: -30°F - 128°F
- UL Listed (US & CA)
- 5 Year warranty



DESIGNLIGHTS 
CONSORTIUM



Applications:

LED High Bay Luminaire lowers energy costs, bulb and ballast replacement costs and also can greatly reduce costly equipment rental when re-lamping HID lamps on and off cycle. LED technology will also eliminate lamp disposal issues due to the mercury content in many HID lamps.

- Outdoor area lighting
- High Bay
- Cold display
- Security Lighting

Packaging: 1 ea = 2 Cartons

Light: 15" x 13" x 13.3"

Shade: 21.7" x 21.7" x 24.8"
(2 shades per carton)

Technical Specifications			
Luminaire Type	LED High Bay	Mounting	Pendant
Bulb Material	Aluminum Alloy	LEDs:	Cree XLM LEDs
Power Consumption	150W	Beam Angle	90°
Lumens	11950 Lm	Dimmable	No
Efficacy	79 LPW	Replaces	400W HID
Rated LED Life	>50,000 Hrs.	CCT	5000K/4000K
Power Factor:	>.987	CRI:	73
IR / UV	None	Mercury/Lead Content	None
Warranty	5 year Limited	Dimensions	20" X 20"

Note: All specification information falls within a $\pm 2\%$ range and is subject to change without notice.

NOTE: Light Efficient Design is providing this information to the general public. Please note that all products contained herein are trademarked, copyrighted, and/or have patents pending. Any use of these designs is strictly prohibited without prior written consent. Light Efficient Design protects its proprietary information vigorously in the courts of the United States of America.